

TECHNICAL SPECIFICATION

1. GENERAL

1.1 Scope

Product Name	Part Number
Wideband Indoor SISO Omni-directional Antenna 1×N-Female,698-2700MHz	103000054


2. CONSTRUCTION and PARAMETERS

2.1 Product Appearance




2.2 Reference Pattern

698-960/1710-2200/2300-2700MHz



Horizontal Pattern



Vertical Pattern

2.3 Electrical Specifications

Description	Wideband Indoor SISO Omni-directional Antenna 1×N-Female,698-2700MHz		
Frequency Range (MHz)	698-960	1710-2200	2300-2700
Gain (dBi)	≥2.0	≥3.8	≥3.8
Vertical 3dB Beam Width (Deg)	90	70	50
Horizontal 3dB Beam Width (Deg)	360		
VSWR	≤2.0		
Inter-modulation IM3 (dBc)	<-140 (3 rd order, 2 × 43dBm)		
Average Input Power (Watt)	≥ 25		

SUMEC Machinery & Electric Co., Ltd.

SINOMACH|SUMEC Group Corporation 198 Changjiang Road, Nanjing, 210018, China

Tel: +86 25 8453 1729 | www.sumecnavigator.com

Maximum Effective Power Per Port (Watt)	50
Impedance (Ohm)	50
Polarization	Vertical

2.4 Physical Specifications

Connector Type	1×N-Female
Antenna Dimensions (mm)	Φ170×18
Antenna Net Weight (kg)	0.17
Pigtail Length (mm)	100
Reflector Material	Aluminum
Radome Material	ABS / White

2.5 Environmental Specifications

IP Rating	IP65
Relative Humidity (%)	0-95
Temperature Range (°C)	-30 ~ +55
Mounting Type	Ceiling mounted